OXYGEN-FIRED FRONT END FOR GLASS FORMING OPERATION

Publication number: WO03084885

Publication date:

2003-10-16

Inventor:

BAKER DAVID J (US); ADAMS HARRY P (US); JIAN

CHRISTOPHER Q (US); TOTH WILLIAM W (US)

Applicant:

OWENS CORNING FIBERGLASS CORP (US); BAKER

DAVID J (US); ADAMS HARRY P (US); JIÀN

CHRISTOPHER Q (US); TOTH WILLIAM W (US)

Classification:

- international:

C03B7/06; C03B7/00; (IPC1-7): C03B7/06; C03B7/096

- European:

C03B7/06B

Application number: WO2003US08313 20030318 Priority number(s): US20020116432 20020404

Also published as:

EP1499565 (A1) US2003188554 (A1) MXPA04009694 (A) EP1499565 (A0) CA2480115 (A1)

more >>

Cited documents:




US4737178 US4604123 US5169424 EP0789191

Report a data error here

Abstract of WO03084885

A front end for a glass forming operation comprises an open channel (22) and at least one burner (44). The channel has at least one surface (40). The surface has at least one hole (42A) therein. The burner is oriented in the hole at an acute angle relative to the surface. In another embodiment of the invention, the channel has a top (24C) and a pair of sidewalls (28A) each having a surface (40, 46). At least one hole (42A, 42C) is in at least one of the surfaces. The hole is at an acute angle relative to at least one surface. The burner is an oxygen-fired burner. In yet another embodiment of the invention, the top (24C) and sidewalls (28A) each have a super structure surface constructed of refractory material. The channel has an upstream end (30A) and a downstream end (32A). At least one of the surfaces has a plurality of holes therein. The burners extend at an acute angle relative to at least one surface and in a plane extending between the upstream end and the downstream end and perpendicular to at least one surface. Oxygen-fired burners extend axially through corresponding holes.



Data supplied from the esp@cenet database - Worldwide